





输出端  
(OUTPUT)



输入端  
(INPUT)



### Technical parameters of reducer. (技术参数: )

Rated input speed(额定输入速度): 3000rpm

Maximum input speed(最大输入速度): 6000rpm

Maximum output torque(最大输出力矩): 3 X Rated output torque(额定输出力矩)

Maximum axial force (最大轴向力): 4700N

Maximum radial force (最大径向力): 9400N

Torsion rigidity (扭转刚性): 50Nm/arcmin

Precision (背隙):  $\leq P1=3, P2=5$  arcmin


Service life (寿命): 20000h

Operating temperature (工作温度):  $-10^{\circ}\text{C}-90^{\circ}\text{C}$


Protection level (防护等级): IP65

Noise (噪音):  $\leq 65$  dB(A)

Efficiency (效率):  $\geq 97\%$



Customer Approval (客户确认)

	SIZE	<b>FASTON</b>		
	A4			
	SIGNATURE	DATE		
DESIGN			STAGE MARKER	TYPE:
STANDARDIZATION			MASS	FKB142-L1(单级)
REVIEW			PAGE	MOTOR DIMENSIONS:
APPROVER	RD		PROPORTION	$\phi 24-\phi 110-\phi 130-M8$

Ratio(传动比数)	3	4	5	6	7	8	9	10	SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE 规格尺寸如有变更, 恕不另行通知
Rated output torque (额定输出力矩)	342Nm	542Nm	650Nm	550Nm	550Nm	500Nm	450Nm	450Nm	