

Technical parameters of reducer. (技术参数:)

Rated input speed (额定输入速度): 3000rpm

Maximum input speed (最大输入速度): 6000rpm

Maximum output torque (最大输出力矩): 3 X Rated output torque (额定输出力矩)

Maximum axial force (最大轴向力): 3350N

Maximum radial force (最大径向力): 6700N

Torsion rigidity (扭转刚性): 25Nm/arcmin

Precision (背隙): $\leq P1=3, P2=5$ arcmin


Service life (寿命): 20000h

Operating temperature (工作温度): $-10^{\circ}\text{C}-90^{\circ}\text{C}$

Protection level (防护等级): IP65

Noise (噪音): ≤ 63 dB(A)

Efficiency (效率): $\geq 97\%$



Customer Approval (客户确认)

	SIZE	FASTON		
SIGNATURE	DATE	TYPE: FKB115-L1 (单级)		
DESIGN	STAGE MARKER	MOTOR DIMENSIONS: ø24-ø110-ø130-M8		
STANDARDIZATION	MASS			
REVIEW	PAGE	PROPORTION		
APPROVER	DATE			

Ratio (传动比数)	3	4	5	6	7	8	9	10
Rated output torque (额定输出力矩)	208Nm	290Nm	330Nm	300Nm	300Nm	260Nm	230Nm	230Nm

SPECIFICATIONS ARE SUBJECT TO CHANGE
WITHOUT PRIOR NOTICE
规格尺寸如有变更, 恕不另行通知