


输入端

输出端



### Technical parameters of reducer. (技术参数: )

Rated input speed(额定输入速度): 3000rpm

Maximum input speed(最大输入速度): 6000rpm

Maximum output torque(最大输出力矩): 3 X Rated output torque(额定输出力矩)

Maximum axial force (最大轴向力): 4700N

Maximum radial force (最大径向力): 9400N

Torsion rigidity (扭转刚性): 50Nm/arcmin

Precision (背隙):  $\leq P1=5, P2=7$  arcmin

Service life (寿命): 20000h

Operating temperature (工作温度):  $-10^{\circ}\text{C}-90^{\circ}\text{C}$

Protection level (防护等级): IP65

Noise (噪音):  $\leq 65$  dB(A)

Efficiency (效率):  $\geq 94\%$

Customer Approval (客户确认)

非标法兰

		SIZE	<b>FASTON</b>		
		A4			
	SIGNATURE	DATE			
DESIGN			STAGE MARKER		TYPE:
STANDARDIZATION			MASS		FKB142-L2(双级)
REVIEW			PAGE		MOTOR DIMENSIONS:
APPROVER	RD		PROPORTION		$\phi 24-\phi 110-\phi 130-M8$

Ratio(传动比数)	15	16	20	25	35	40	50	70	100	SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE 规格尺寸如有变更, 恕不另行通知
Rated output torque (额定输出力矩)	342Nm	543Nm	542Nm	650Nm	550Nm	542Nm	650Nm	550Nm	450Nm	