

### Technical parameters of reducer. (技术参数: )

Rated input speed(额定输入速度): 3000rpm

Maximum input speed(最大输入速度): 6000rpm

Maximum output torque(最大输出力矩): 3 X Rated output torque(额定输出力矩)

Maximum axial force (最大轴向力): 1650N

Maximum radial force (最大径向力): 3250N

Torsion rigidity (扭转刚性): 14Nm/arcmin

Precision (背隙):  $\leq P1=3, P2=5$  arcmin


Service life (寿命): 20000h

Operating temperature (工作温度):  $-10^{\circ}\text{C}-90^{\circ}\text{C}$

Protection level (防护等级): IP65

Noise (噪音):  $\leq 60\text{dB(A)}$

Efficiency (效率):  $\geq 97\%$



Customer Approval (客户确认)

		SIZE	<b>FASTON</b>		
		A4			
		SIGNATURE	DATE		
DESIGN			STAGE MARKER		TYPE:
STANDARDIZATION			MASS		FKB090-L1
REVIEW			PAGE		MOTOR DIMENSIONS:
APPROVER			PROPORTION		$\phi 24-\phi 110-\phi 130-M8$

Ratio(传动比数)	3	4	5	6	7	8	9	10
Rated output torque (额定输出力矩)	130Nm	140Nm	160Nm	140Nm	140Nm	120Nm	100Nm	100Nm

SPECIFICATIONS ARE SUBJECT TO CHANGE  
WITHOUT PRIOR NOTICE  
规格尺寸如有变更, 恕不另行通知